

CORA

Reverse Cycle Split System



ENERGY RATING		
6.0 ★	HOT climate	3.5 ★
5.0 ★	AVERAGE climate	3.0 ★
5.5 ★	COLD climate	3.0 ★

25 Class Model

STYLED TO PERFORM

A reliable performer, the Cora series comes fully featured with whisper quiet operation and without compromise on style.

R32 refrigerant
66% lower 'Global Warming Potential Factor' than R410A providing less risk of harm to the environment.

Inverter powerful operation
Features a cooling or heating boost for a 20 minute period, even if the unit is already operating at high capacity.

Precision control
Room temperature can be set in increments of 0.5°C to ensure optimal comfort all year round.

Coanda airflow
Discharge louvres are designed to stream air upwards along the ceiling for rapid cooling and uniform temperature distribution.


Intelligent comfort
The 2-Area Intelligent Eye* helps prevent cold draughts and enables energy saving operations when the room is unoccupied.

Air purification
Fitted with an enzyme blue deodorising air purification filter that traps microscopic particles, decomposes odours and even deactivates bacteria.

Technology

SAW EDGE CROSS FLOW FAN
Large diameter rotor with aerofoil blade design delivers larger volumes of air more quietly than ever before.

NEW ODM MOTOR
Compact 10 pole DC outer rotor motor delivers higher torque more efficiently.



REDESIGNED HEAT EXCHANGER
Slit type fin design with Ø5mm piping increases heat exchange area for improved capacity output and energy performance.

2-AREA INTELLIGENT EYE
Gives you the option to direct airflow either towards or away from you for draught free comfort. If no occupation is detected, the air conditioner operates in energy saving mode.

*2-Area Intelligent Eye only applicable to 20-46 Class Models.

SPECIFICATIONS



Indoor Unit		FTXV20W2VMA	FTXV25W2VMA	FTXV35W2VMA	FTXV46W2VMA	FTXV50W2VMA	FTXV60W2VMA	FTXV71W2VMA	
Outdoor Unit		RXV20W2VMA	RXV25W2VMA	RXV35W2VMA	RXV46W2VMA	RXV50W2VMA	RXV60W2VMA	RXV71W2VMA	
Rated Capacity	Cool (kW)	2.0	2.5	3.5	4.6	5.0	6.0	7.1	
	Heat (kW)	2.7	3.2	3.7	4.7	6.0	7.2	8.0	
Capacity Range	Cool (kW)	0.9-2.8	0.9-3.7	0.9-4.2	0.9-5.5	1.1-6.7	1.1-7.5	2.0-8.9	
	Heat (kW)	0.9-4.4	0.9-5.4	0.9-5.5	1.0-6.7	1.0-8.0	1.0-9.8	2.0-10.8	
Indoor Airflow Rate (H)	Cool (l/s)	152	173	175	203	267	310	310	
	Heat (l/s)	157	168	183	202	287	333	328	
Indoor Fan Speeds		5 steps, quiet and automatic							
Star Rating (Hot/Avg/Cold) ZERL (Residential)	Cool	5/4.5/4.5	6/5/5.5	5/4.5/4.5	4/3.5/4	5/4.5/5	4/4/4	3.5/3/3	
	Heat	3/3/2.5	3.5/3/3	3/2.5/2.5	3/2.5/2.5	3.5/3/2.5	3.5/3/2.5	3/2.5/2	
Front Panel Colour		White							
Power Supply		1 phase, 220-240V, 50Hz							
Power Input (Rated)	Cool (kW)	0.40	0.49	0.81	1.20	1.14	1.52	1.93	
	Heat (kW)	0.53	0.64	0.77	1.11	1.30	1.63	1.88	
E.E.R./C.O.P	Cool/Heat	5.00/5.09	5.10/5.00	4.32/4.81	3.83/4.23	4.39/4.62	3.95/4.42	3.68/4.26	
TCSPF (Residential)	Hot/Avg/Cold	6.95/6.13/6.23	7.69/6.85/7.02	6.64/6.20/6.42	5.67/5.28/5.54	6.88/6.35/6.72	5.91/5.56/5.89	5.38/4.80/4.96	
HSPF (Residential)	Hot/Avg/Cold	4.65/4.57/4.34	5.10/4.86/4.53	4.63/4.47/4.13	4.81/4.43/4.04	5.12/4.72/4.19	5.00/4.57/4.02	4.78/4.39/3.91	
A.E.E.R./A.C.O.P	Cool/Heat	4.90/5.02	5.02/4.94	4.28/4.76	3.81/4.20	4.36/4.59	3.93/4.40	3.62/4.19	
Dimensions (HxWxD)	Indoor (mm)	285x770x223				295x990x263			
	Outdoor (mm)	550x675x284				695x930x350			
Weight	Indoor (kg)	9	9	9	9	13	13	13	
	Outdoor (kg)	28	30	30	51	54	54	60	
Compressor Type		Hermetically Sealed Swing Type							
Refrigerant Type		R32							
Max Pipe Length	(m)	20	20	20	30	30	30	30	
Max Level Difference	(m)	15	15	15	20	20	20	20	
Pipe Sizes	Liquid (mm)	6.4	6.4	6.4	6.4	6.4	6.4	6.4	
	Gas (mm)	9.5	9.5	9.5	12.7	12.7	12.7	15.9	
Outdoor Operating Range	Cool (°CDB)	-10 to 46							
	Heat (°CWB)	-15 to 18							
Indoor Sound Level (H/SL)	Cool (dBA)	38/19	42/19	42/19	44/26	45/28	48/29	49/30	
	Heat (dBA)	39/20	40/20	42/20	43/26	45/28	48/29	49/30	
Outdoor Sound Level (H/SL)	Cool (dBA)	46/43	47/43	49/44	47/44	47/44	49/45	53/49	
	Heat (dBA)	47/44	48/44	49/45	48/45	48/45	52/45	54/49	
Outdoor EPA Sound Power Level (H)	Cool (dBA)	58	59	61	59	59	61	65	
	Heat (dBA)	59	60	61	60	60	64	66	

All models feature built-in Demand Response Enabling Device (DRED) compliant to AS/NZS 4755.3.1:2012.

ZERL (Residential) refers to 'Zoned Energy Rating Label' residential star rating as outlined in the GEMS 2019 Determination.

Notes:

- The Rated Capacity, Power Input and Running Current are determined under conditions T1 (cooling) or H1 (heating) of AS/NZS 3823.1.1
Cooling: Indoor temp: 27°CDB/19°CWB, Outdoor temp: 35°CDB/24°CWB
Heating: Indoor temp: 20°CDB/15°CWB, Outdoor temp: 7°CDB/6°CWB
- The cooling (or heating) output capacity will be reduced below the rated value as the outdoor temperature approaches the maximum (or minimum) outdoor temperature operating range limit.
- The specifications, designs & information in this flyer are subject to change without notice. Unit colours shown are as close as possible to actual unit colours. Colours depicted in this flyer may vary slightly.

CONTACT



Daikin Australia Pty Limited ABN 62 000 172 967

For all Sales enquiries, email: sales@daikin.com.au

For Customer Service or Technical Support, call: 1300 368 300

Want to learn more about our product range?

Subscribe to our YouTube Channel or go to daikin.com.au

